

# CleanStrip ESD™ High Performance Floor Stripper

## *Restore ESD Properties of Old ESD Flooring*

Your ESD flooring is not just any flooring product, but a functioning, technical component of your static-sensitive work environment. Using the wrong maintenance products on your floor can render it ineffective. Protect your investment by using ProtectOhm ESD™, specifically designed for use in maintenance programs whose goal is to reduce static electricity build-up and increase the conductivity of surfaces in areas where sensitive electronic components are being used or manufactured.

Residues from detergents, dirt, and floor finishes can quickly reduce the performance of any ESD Flooring. CleanStrip ESD™ is designed to effectively dissolve and remove these residues to keep your floor performing at its peak. It is formulated from top quality water-miscible solvents and contains less than 1% solids at concentration, so it leaves no residue. Old build-up can be easily removed using CleanStrip ESD™ and an auto-scrubber, using a standard stripping pad.

## **Use**

Dilute 16 ounces of CleanStrip ESD™ (1:8) for routine stripping (1-10 coats), 32 ounces (1:4) for medium build-up (11-15 coats), 64 ounces (1:2) for heavy build up (15-25 coats) or 128 ounces (1:1) for severe build-up (25+ coats) per gallon of **COLD water only**.

Apply stripping solution with a mop, and let it stand for five minutes. Removing heavy finish build-up may require scrubbing with a 175-300 Rpm buffing machine equipped with a black stripping pad.

Remove the dissolved finish and solution with a wet vacuum. Any residual dissolved floor finish not removed by vacuuming should be removed by light rinsing or damp mopping.

Allow the floor to dry thoroughly before applying any new finish such as StaticStop's DuraShield ESD™ floor finish.

**CleanStrip ESD™ is not recommended for use on Asphalt Tile or older Linoleum Tiles as it may remove the dye particularly from dark colored tiles.**



a division of SelecTech, Inc.  
33 Wales Ave, Suite F.  
Avon, MA 02322

877-738-4537

[www.staticstop.com](http://www.staticstop.com)

# CleanStrip ESD™ High Performance Floor Stripper

## Restore ESD Properties of Old ESD Flooring

SPECIFICATIONS		SAFETY INFORMATION	
Active Ingredients	Water miscible solvents, amine complexes, alcohol ethoxylates	Health	2
		Flammability	0
		Reactivity	0
		Personal Protection	B
pH	12.8 - 13.2	CAUTION: This product contains a strong alkaline ingredient.	
Free Ammonia	None	If ingested, give vinegar, juice of lemon, grapefruit, or orange freely . Do NOT induce vomiting. <b>Get immediate medical attention.</b>	
Free Alkali	0.5%	If contact with skin or eyes occurs, flush with large volumes of water. <b>Get immediate medical attention.</b>	
Free Acid	None	Contains 2-Butoxy Ethanol CAS #111-76-2, and 2-Amino Ethanol CAS #141-43-5.	
Phosphates	None	For detailed information, consult MSDS sheet.	
Abrasives	None		
Color	Light Yellow		
Odor	Moderate		
Solubility in Water	100%		
Freeze/Thaw Stability	3 cycles		
Shelf Life	Min. 1 year (30°F - 125°F.)		
Flash Point Above	200° F.		
Weight Per Gallon	8.2 lbs		
Biodegradable	Yes		
Soil Suspension	Excellent		



a division of SelecTech, Inc.  
33 Wales Ave, Suite F.  
Avon, MA 02322

877-738-4537

[www.staticstop.com](http://www.staticstop.com)